

## AC-225

### Advanced Scalable Networked Access Controller

The state-of-the-art single/dual door AC-225 networked access controller is the backbone of medium scale security systems handling up to 30,000 users and 4092 doors. Driven by Rosslare's powerful, flexible and easy to use software, the system provides an ideal, modular and expandable solution for commercial and institutional needs. It provides seamless integration with Rosslare's range of RFID Proximity, PIN, PIN & PROX, Smartcard and biometric readers with Rosslare's selection of RFID credentials.

### General Description

AC-225 is suitable for applications with up to 30000 users across a modular 4092 doors, allowing maximum flexibility for securing a growing enterprise.

Each AC-225 Access Control Unit (ACU) supports two readers (In/Out) of various formats including standard Wiegand 26-bit. Installations can also have one reader per door.

The AC-225 is ready for installation with a mountable & lockable metal enclosure integrated with transformer, power supply/charger, sounder and control board.

Using onboard RS-232, Ethernet TCP/IP, and PSTN, multiple local or remote site door sub-networks can connect to the AS-525 AxTrax Client/Server PC software running on Microsoft® Windows® 98/ME & NT/2000/XP operating systems.



### Main Features

- Up to 30,000 users with access rights for every panel, across optional 4092 modular doors in a system
- 20,000, FIFO, history event log, when offline
- Full intelligent logic interconnection of inputs, outputs, readers, and more
- With MD-IO84 IO expansion, additional 8 inputs, 4 outputs
- With MD-D02 2-Door expansion, 2 readers with 4 inputs, 4 outputs
- Supervised, 4 state end-of-line inputs
- Onboard TCP/IP networking (AC-225IP version)
- Panel supports both 1 door (In/Out) and 2 door (In/Out, In/In and Out/Out) configurations
- Real-time clock keeps time for up to 2 weeks without power. No batteries to replace
- Cable cut tamper detection function for readers, and cover tamper detection for the enclosure
- Pre-installed enclosure components:
  - Transformer, dual power supply/charger unit for panel and Lock devices
  - Sounder unit
  - Space for a 7AH SLA backup battery
  - Tamper switch

### AS-525 CLIENT/SERVER SOFTWARE HIGHLIGHTS

- AS-525 AxTrax is based on SQL Express 2005 database
- Each ACU subnet, consisting of up to 32 ACUs, may be connected to a PC running the AS-525 server PC software
- Enables management of user data, photo with custom fields, access rights, alarms, strike times, and door modes, from a central location
- Used for continuous event monitoring, or periodically for batch downloading of event data, administration and maintenance
- Other PC's on the network may connect to the server by installing the AS-525 PC software *client* application
- Produces reports from acquired data, such as entry and exit times, and by alarm type with filters for user(s), location, and time
- The AS-525 AxTrax software is available in a large selection of languages
- Highly user friendly and straight-forward interface provides an easy and fast setup

# AC-225 Advanced Scalable Networked Access Controller



## Product Specifications

ELECTRICAL CHARACTERISTICS	
● ACU Power Supply Voltage:	12VDC, regulated from built-in PS-33 regulated power supply / Charger module
● ACU Power Supply Max Current:	Panel output: 2A input current limitation (PS-33) Lock output: 3A
● Relays:	4 fully programmable 5A, N.O. and N.C. relay outputs 4 expandable outputs with optional MD-IO84 or MD-D02
● Battery Charger:	12V sealed lead acid (SLA) up to 7Ah (PS-33)
● Maximum Current for Readers:	300mA at 12VDC
OPERATIONAL CHARACTERISTICS	
● Capacity:	30,000 Users
● History Event Log Size:	20,000 Events
● Inputs:	4 Supervised, dual-resistor, 2 state end-of-line inputs, Hi-impedance, active low 5VDC 8 supervised expandable inputs with optional MD-IO84 or 4 supervised expandable inputs with optional MD-D02
● Readers:	Two Wiegand 26/32/34/37/40 bit / C&D reader ports with tamper and LED control, 4,6 and 8 bit keypad transmission support
● Connectivity:	RS-485/232, Dial-up (using MD-N33), onboard TCP/IP (AC-225IP version)
● Networking:	32 Units/subnet, 1023 subnets (4092 doors max. with MD-D02) using AS-525 AxTrax software
● Audio/Visual:	Built-in sounder (Alarm, Chime, Bell), 11 on-board and 3 P.S. LEDs
● Modes of Operation:	Single Door (In/In), Dual Door (In/Out)
● Time Zones and groups:	32 multiple segment time zones, 64 holidays, 30,000 access groups
● Anti-Pass Back:	Local and Global anti-pass back (soft / hard), with 'forgive' option
● Special Features:	Interlock, first person delay, auto relock, scheduled outputs operation, 4 programmable site codes, Extended unlocked time, fully interconnectedness.
● Security Modes:	Normal and Secure
● Firmware Upgrade:	Local / Remote, Through AS-525 AxTrax PC software
PHYSICAL CHARACTERISTICS	
● ACU Board Dimensions:	168mm x 121mm (6.61" x 4.76")
● Enclosure:	Metal, locked 326mm x 263mm x 97mm (12.8" x 10.4" x 3.82")
● Weight:	2.4kg (5.3 lbs)
ENVIRONMENTAL CHARACTERISTICS	
● Operating Environment:	Indoor installation only
● Operating Temperature:	0°C to 49°C (32°F to 120°F)
● Operating Humidity:	0 to 85% (non-condensing)
● RFI Protection:	> 20 V/m up to 1000 MHz

## System Components

AC-225 is compatible with a range of Rosslare accessories, including a diverse selection of readers and accessories; two extension boards complement the AC-225: MD-IO84 and MD-D02.



## Additional Information

The following models are available:

- AC-225
- AC-225IP (onboard TCP/IP module)
- AC-225-PCBA
- AC-225IP-PCBA

The following Expansions are available:

- MD-IO84 (input/output expansion module)
- MD-D02 2-Door Expansion (2 Readers, 4 Inputs, 4 Outputs)

The AC-225 is covered by Rosslare's 2-year Limited Product Warranty. For sales information or product documentation, please visit our website: <http://www.rosslaresecurity.com>.