

## AC-525

### Video Integrated Networked Access Controller

**AC-525 is a highly advanced networked control panel that offers unified Access Control and Digital Video Recording at MPEG-4 format and web server components.**

**This fully featured Access Controller manages 30,000 users across two doors (expandable up to 4 doors). The digital Video Server component supports 2 analog cameras with PTZ, and voice, web server and a local DVR using USB storage device. This cost effective 2-in-1 cuts down integration and installation costs and is easy to configure and operate.**

### General Description

The system features a powerful ARM9-based architecture with DSP, which is a leading technology video chipset including a web server and DVR running on Embedded Linux OS.

All panel features can be accessed with a single Ethernet port and IP Address, and each panel is expandable by an additional 2-door module (MD-D02) or 8/4 input/output module (MD-IO84).

USB storage devices can be connected for high capacity local DVR on the edge.

Multiple panels are managed using Rosslare's modular and scalable client / server software AS-525 AxTrax for Access Control Management and ViTrax for NVR Management, storage and Surveillance.



### Main Features

- Compact full featured integration with complete 2-door physical access control interface including 2 channels of digital multimedia. Install less hardware units, which are dedicated to both fields.
- Advanced, fully featured Access Control and analog cameras integration to trigger video recording upon any event in the access control panel.
- Compatible with almost any type of Analog Cameras, Microphones and Speakers for Video and Voice recording and real-time monitoring.
- Supports ISO Standard MPEG-4 IPP video streaming. For connecting to remote NVR hardware or software
- Supports USB based storage for Edge DVR
- Embedded Linux OS Based web server lets you access the web-server with IE Browser
- Available with custom lockable housing with sounder, AC/AC transformer with space for up to 7Ah Sealed Lead-Acid Backup Battery.

#### OPTIONS FOR EDGE DATA STORAGE

- On-Board pre-alarm and post event timers and custom recording preferences.
- On-Board USB 2.0 connection for external USB 2.0 compliant flash drive or Hard Disk for Edge DVR.

#### APPLICATIONS

- Perfect for educational, financial, commercial, health, transportation, military and many other applications
- Audio Visual Intercom & Video Verification of Access Control
- Remote LAN / WAN Video Surveillance and Digital Multimedia Recording

# AC-525 Video Integrated Networked Access Controller



## General Specifications

<b>PC Server Software</b>	For AS-525 AxTrax™ and AS-525AV ViTrax™ Client/Server Platforms
• <b>Operating System:</b>	Microsoft® Windows® XP – for both Server & Client PCs
• <b>PC Minimum Requirement:</b>	Pentium IV 3.0GHz / 512 MB RAM / CD or DVD RW/ 100 MB HDD Space / 100 MBps TCP/IP LAN Card / RS232 D9 Serial Ports.
• <b>Database:</b>	Microsoft® MS SQL Server & Proprietary Multimedia Data Server
<b>Panel Features- Access Control</b>	
• <b>Supports Multiple Reader Modes:</b>	2 Reader interface ports with Tamper and LED control, expandable to 4 doors using MD-D02 expansion unit
• <b>Relay Outputs</b>	4 Form-C 5 Amp Relays (expandable with up to 4 outputs and 8 inputs with MD-IO84 IO expansion unit)
• <b>Analog Inputs</b>	4 On-board EOL supervised Analog Inputs
• <b>Serial Communication</b>	1 On-board RS-485 Port for direct sub-networking
• <b>TCP/IP Ethernet Adapter</b>	On-Board 10/100 MBPS Ethernet Port
• <b>Event log size</b>	20,000 history events per panel
• <b>User Capacity:</b>	30,000 Users associated in logical Groups
• <b>Networking:</b>	Up to 1023 Networked Panels per AxTrax PC Server: Supports TCP/IP Sub-networks over LAN /WAN – Drivers Included, Supports PSTN Modem, and RS485 Sub-networks.
• <b>Time Zones:</b>	Up to 32 Time Zones can be assigned to Access / Reports / Update
• <b>Holidays:</b>	Up to 64 Holiday Dates
<b>Panel Features- Digital Video</b>	
• <b>2-Analog Video Inputs</b>	2 Encoders on-board that stream MPEG-4 at up to 30 fps / single channel in D1 Resolution or 8 fps for 2 Channels at D1 Resolution, scalable down to QCIF.
• <b>PTZ controls</b>	2 Local PTZ serial ports
• <b>Audio Inputs</b>	2 Analog mono microphone inputs
• <b>USB Port</b>	USB 2.0 supports Flash drives USB Disk for Edge DVR
• <b>Embedded Linux</b>	Web Server to view and configure the Video Server using IE

\*Microsoft and Windows are trademarks of Microsoft Corporation.

## System Components

The system supports Rosslare's MD-D02 2-door expansion, MD-IO48 IO Expansion, wide range of readers on standard Wiegand communications and different types of accessories.



## Additional Information

The AC-525 is a high-quality electronic product developed and manufactured under ISO9001:2000. It is covered by the RSP 2-year Limited Product Warranty.

Please visit our website for documentation and sales information: <http://www.rosslaresecurity.com/>



Distributed by:

VERSION 2.0  
5501-0010401-01  
© Copyright Rosslare 2005-2008

